

L1 ANSWER 8 OF 10 CA COPYRIGHT 2003 ACS
 AN 127:210403 CA
 TI Implantable tooth replacement with ceramic abutment of zirconium oxide
 IN Wohlwend, Arnold
 PA Wohlwend, Arnold, Switz.
 SO PCT Int. Appl., 41 pp.
 CODEN: PIXXD2
 DT Patent
 LA German
 IC ICM A61C008-00
 ICS A61C013-00; A61K006-06
 CC 63-7 (Pharmaceuticals)
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	WO 9730654	A1	19970828	WO 1997-EP871	19970223
	W: AU, CA, DE, JP, NO, US				
	RW: AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE				
	AU 9717945	A1	19970910	AU 1997-17945	19970223
PRAI	CH 1996-482		19960222		
	CH 1996-1471		19960612		
	WO 1997-EP871		19970223		
AB	<p>An implantable tooth replacement consists of an implant which can be secured in a jawbone, an abutment made of a ceramic material which can be secured to the implant by a securing screw, a tooth prosthesis, e.g. a crown or bridge, and a securing means for fixing the abutment to the tooth prosthesis. The ceramic material has a fracture toughness of ≥ 6 MPa/m² and a flexural strength of ≥ 700 MPa, and consists of $\geq 90\%$ ZrO₂. These phys. properties are much superior to those of conventional sintered Al₂O₃ abutments. Other ceramics with similar properties, such as Si₃N₄ and TiC, or ceramics reinforced with fibers such as SiC fibers or whiskers, may also be used. Use of partially sintered or green ZrO₂ facilitates machining the abutment to shape extraorally.</p>				
ST	denture abutment zirconium oxide ceramic				
IT	Alkaline earth oxides				
	Rare earth oxides				